

Not to scale

**02-082 – Bulb Seal (PVC)**



**02-154 – Door Rubber (400-931)**

Suitable for 700-130, 400-931



**02-218 – V Seal (700-207)**

Suitable for 700-617



**02-231 – V Seal**

Suitable for 700-231, 700-235,  
700-286, 700-407, 700-629



**02-419 – Bulb Seal (Inner Sash)**

Suitable for LSS-401, 370-126




**02-681 – V-Seal (EPDM)**

Suitable for 700-555,  
700-541, 700-111,  
700-115, 700-126,  
700-168, 700-185,  
700-246



**03-236 – Transom Stop (0.8mm thick)**



**04-108 – Glazing Wedge**



**04-116 – Glazing Wedge**



**04-118 – Glazing Wedge (615 System)**



Up to date stock availability can be viewed at [www.lidco.com.au/indices](http://www.lidco.com.au/indices)

# COMMERCIAL RANGE 710 SYSTEM

## Emporia™ 100mm/150mm Centre Glazed

Not to scale

04-142 – Glazing Wedge



04-222 – Captive Wedge (PVC)



04-222E – Captive Wedge (EPDM)



04-223 – Captive Wedge (PVC)



04-223E – Captive Wedge (EPDM)



04-224 – Glazing Wedge (PVC)



04-224E – Glazing Wedge (EPDM)



04-230E – Glazing Wedge (EPDM)



04-233E – Glazing Wedge (EPDM)



04-234 – Glazing Wedge (400-661)

Suitable for 400-661



Up to date stock availability can be viewed at [www.lidco.com.au/indices](http://www.lidco.com.au/indices)


Not to scale

**04-235E – Glazing Wedge (EPDM)**



**05-062 – Corner Stake (400-661)**

Suitable for 400-661,  
LSS 401



**05-065 – Corner Stake (900-065)**

Suitable for 900-065



**05-146 – Corner Stake (400-655)**

Suitable for 400-655,  
370-126, 900-019





Up to date stock availability can be viewed at [www.lidco.com.au/indices](http://www.lidco.com.au/indices)

# COMMERCIAL RANGE 710 SYSTEM

## Emporia™ 100mm/150mm Centre Glazed



Not to scale

Casement Window Stay (Stainless Steel)  	Part Number	Length	Maximum Opening Angle	Maximum Sash Weight	Maximum Sash Width	Notes
	18-171	230mm	90°	25kg	800mm	
	18-171NF	230mm	90°	25kg	***	Non-friction
	18-183	430mm	90°	40kg	1000mm	
	18-183NF	430mm	90°	40kg	***	Non-friction

For **Casement Window** 373, 413, 710, 715, and 718 Systems

Awning Window Stay (Stainless Steel)  	Part Number	Length	Maximum Opening Angle	Maximum Sash Weight	Maximum Sash Height	Notes
	18-172	200mm	40°	10kg	600mm	
	18-172NF	200mm	40°	10kg	***	Non-friction
	18-173	350mm	30°	20kg	800mm	
	18-173NF	350mm	30°	20kg	***	Non-friction
	18-174	500mm	25°	30kg	1800mm	
18-174NF	500mm	25°	30kg	***	Non-friction	

For **Awning Window** 373, 413, 710, 715, and 718 Systems

Awning Window Stay (Aluminium)  	Part Number	Length	Maximum Opening Angle	Maximum Sash Weight	Maximum Sash Height	Notes
	18-190	230mm	45°	6kg	750mm	
	18-192	230mm	45°	10kg	***	Non-friction
	18-191	330mm	35°	9kg	1000mm	
	18-187	420mm	20°	15kg	1800mm	
	18-187	420mm	20°	20kg	1500mm	
18-187	420mm	20°	43kg	1200mm		

For **Awning Window** 373, 413, 710, 715, and 718 Systems

\*\*\* Based on weight rating of the winder

Up to date stock availability can be viewed at [www.lidco.com.au/indices](http://www.lidco.com.au/indices)

Not to scale

18-201 – Stainless Steel Restrictor



19-300L – 6mm Cam Handle (Left)



19-300R – 6mm Cam Handle (Right)



19-301L – 6mm Lockable Cam Handle (Left)



19-301R – 6mm Lockable Cam Handle (Right)



Up to date stock availability can be viewed at [www.lidco.com.au/indices](http://www.lidco.com.au/indices)